



Bronze Alloys

Safety Data Sheet

Date of issue: 8/10/22 Version: 2.0

SECTION 1: IDENTIFICATION

- 1.1. Product Identifier**
Product Form: Mixture
Product Name: Bronze Alloys
Synonyms: Bar, Sheet, Plate, Pipe, Tubing, and Structural
- 1.2. Intended Use of the Product**
Solid product, various forms and uses
- 1.3. Name, Address, Telephone of the Responsible Party**
Alaskan Copper Companies, Inc.
27402 72nd Avenue South
Kent, Washington 98032
T (206) 623-5800; (800) 552-7661
acbsea@alaskancopper.com
http://alaskancopper.com
- 1.4. Emergency Telephone Number**
Emergency Number: (800) 552-7661
In the case of fire, explosion or spill, call 911

SECTION 2: HAZARDS IDENTIFICATION

- 2.1. Classification of the Substance or Mixture**
GHS-US classification Not classified
- 2.2. Label Elements**
GHS-US Labeling **No labeling applicable**
- 2.3. Other Hazards**
Solid metal products are generally classified as "articles" and do not constitute hazards in solid form. The materials present in this product in their powdered forms present aquatic toxicity to the environment, pyrophoricity, flammability, self-heating capabilities, carcinogenicity, water reactivity, and acute toxicity. When processed or where dust is generated a combustible dust hazard may be present. Avoid generating dust, generating sparks, ignition sources, and take all precautions. Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath. Under normal use and handling of the solid form of this material there are few health hazards. Cutting, welding, melting, grinding etc. of these materials will produce dust, fume or particulate containing the component elements of these materials. Exposure to the dust, fume or particulate of these materials may present significant health hazards. Exposure to dust or fume may cause irritation of the eyes, skin and respiratory tract. Fine particulates dispersed in air may present an explosion hazard.
- 2.4. Unknown Acute Toxicity (GHS-US)** **No data available**

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Mixture

Name	Product Identifier	% (w/w)	GHS-US classification
Copper	(CAS No) 7440-50-8	55 - 99.9	Comb. Dust
Aquatic Acute 1, H400			
Aquatic Chronic 3, H412			
Zinc	(CAS No) 7440-66-6	0.01 - 45	Comb. Dust
Tin	(CAS No) 7440-31-5	0.01 - 25	Comb. Dust
Lead	(CAS No) 7439-92-1	< 25	Carc. 1B, H350
Repr. 1A, H360			
STOT RE 1, H372			
Aquatic Acute 1, H400			
Aquatic Chronic 1, H410			
Aluminum	(CAS No) 7429-90-5	<= 16	Comb. Dust Flam. Sol. 1, H228
Manganese	(CAS No) 7439-96-5	<= 14	Comb. Dust
Iron	(CAS No) 7439-89-6	<= 6.5	Comb. Dust
Nickel	(CAS No) 7440-02-0	< 6	Comb. Dust
Skin Sens. 1, H317			
Carc. 2, H351			
STOT RE 1, H372			
Aquatic Chronic 3, H412			
Cobalt	(CAS No) 7440-48-4	0.01 - 3	Comb. Dust
Acute Tox. 4 (Oral), H302			
Eye Irrit. 2A, H319			
Resp. Sens. 1B, H334			
Skin Sens. 1, H317			
Carc. 1B, H350			
Repr. 2, H361			
Aquatic Chronic 1, H410			
Phosphorus elemental	(CAS No) 7723-14-0	<= 1.5	Acute Tox. 1 (Oral), H300
Acute Tox. 2 (Dermal), H310			
Acute Tox. 4 (Inhalation: dust, mist), H332			
Aquatic Acute 3, H402			
Flam. Sol. 1, H228			

Aquatic Chronic 3, H412			
Silicon	(CAS No) 7440-21-3	<= 1.5	Comb. Dust
Antimony	(CAS No) 7440-36-0	<= 0.35	Comb. Dust
Acute Tox. 3 (Oral), H301			
Carc. 2, H351			
Aquatic Chronic 3, H412			

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: IF exposed or concerned: Get medical advice/attention. Never give anything by mouth to an unconscious person. **Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Keep at rest and in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Cool skin rapidly with cold water after contact with molten product. Removal of solidified molten material from skin requires medical assistance. Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash with plenty of soap and water. Wash contaminated clothing before reuse. Obtain medical attention if irritation persists.

Eye Contact: Removal of solidified molten material from the eyes requires medical assistance. Immediately rinse with water for a prolonged period (at least 15 minutes) while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Welding, cutting, or processing this material may release dust or fumes that are hazardous.

Inhalation: Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Skin Contact: May cause an allergic skin reaction. Dust from physical alteration of this product causes skin irritation. Causes severe skin burns. Contact with fumes or metal powder will irritate skin. Contact with hot, molten metal will cause thermal burns. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Mechanical damage via flying particles and chipped slag is possible.

Eye Contact: Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: **Copper:** Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever, dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair. Tissue damage of mucous membranes may follow chronic dust exposure. **Tin:** Has been shown to increase incidence of sarcoma in animal tests. Chronic exposure to tin dusts and fume may result in "stannosis", a mild form of pneumoconiosis. **Silver:** Chronic skin contact or ingestion of silver dust, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes. **Nickel:** May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. **Lead:** Exposure can result in lassitude (weakness, exhaustion), insomnia; facial pallor; anorexia, weight loss, malnutrition; constipation, abdominal pain, colic; anemia; gingival lead line; tremor; encephalopathy; kidney disease; hypertension.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention, have product container or label at hand.

SECTION 5 FIRE FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire. Dry sand; Class D Extinguishing Agent (for metal powder fires).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire. Do not use water when molten material is involved, may react violently or explosively on contact with water. Product itself is not explosive but if dust is generated, dust clouds suspended in the air can be explosive.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: A non-combustible material, not considered flammable but will melt above 1700F (927C).

Explosion Hazard: In molten state: reacts violently with water (moisture).

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products:** Oxides of tin. Oxides of nickel. Oxides of copper. Oxides of silicone and carbon. Oxides of lead. Oxides of aluminum. Oxides of silver.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not handle until all safety precautions have been read and understood. Do not breathe vapors from molten product.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely.

For particulates and dust: Avoid actions that cause dust to become airborne during clean-up such as dry sweeping or using compressed air. Use HEPA vacuum or thoroughly wet with water to clean-up dust. Use PPE described in Section 8. Vacuum must be fitted with HEPA filter to prevent release of particulates during clean-up.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: May generate flammable/explosive dusts or turnings when brushed, machined or ground. Use care during processing to minimize generation of dust. Where excessive dust may result, use approved respiratory protection equipment. Heating of product can release toxic or irritating fumes; ensure proper ventilation is employed, proper precautions are enforced, and applicable regulations are followed. Inhalation of fumes may cause metal fume fever.

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust,

fumes.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Alkalis. Metal oxides. Water, humidity. Corrosive substances in contact with metals may produce flammable hydrogen gas.

7.3. Specific End Use(s) No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Nickel (7440-02-0)		
USA ACGIH	ACGIH TWA (mg/m)	1.5 mg/m (inhalable fraction)
USA ACGIH	ACGIH chemical category	Not Suspected as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m)	1 mg/m
USA NIOSH	NIOSH REL (TWA) (mg/m)	0.015 mg/m
USA IDLH	US IDLH (mg/m)	10 mg/m
Alberta	OEL TWA (mg/m)	1.5 mg/m
British Columbia	OEL TWA (mg/m)	0.05 mg/m
Manitoba	OEL TWA (mg/m)	1.5 mg/m (inhalable fraction)
New Brunswick	OEL TWA (mg/m)	1 mg/m
Newfoundland & Labrador	OEL TWA (mg/m)	1.5 mg/m (inhalable fraction)
Nova Scotia	OEL TWA (mg/m)	1.5 mg/m (inhalable fraction)
Nunavut	OEL STEL (mg/m)	2 mg/m
Nunavut	OEL TWA (mg/m)	1 mg/m
Northwest Territories	OEL STEL (mg/m)	3 mg/m (inhalable fraction)
Northwest Territories	OEL TWA (mg/m)	1.5 mg/m (inhalable fraction)
Ontario	OEL TWA (mg/m)	1 mg/m (inhalable)
Prince Edward Island	OEL TWA (mg/m)	1.5 mg/m (inhalable fraction)
Québec	VEMP (mg/m)	1 mg/m
Saskatchewan	OEL STEL (mg/m)	3 mg/m (inhalable fraction)
Saskatchewan	OEL TWA (mg/m)	1.5 mg/m (inhalable fraction)
Yukon	OEL STEL (mg/m)	3 mg/m
Yukon	OEL TWA (mg/m)	1 mg/m
Copper (7440-50-8)		
USA ACGIH	ACGIH TWA (mg/m)	0.2 mg/m (fume)
USA OSHA	OSHA PEL (TWA) (mg/m)	0.1 mg/m (fume) 1 mg/m (dust and mist)
USA NIOSH	NIOSH REL (TWA) (mg/m)	1 mg/m (dust and mist) 0.1 mg/m (fume)

USA IDLH	US IDLH (mg/m)	100 mg/m (dust, fume and mist)
Alberta	OEL TWA (mg/m)	0.2 mg/m (fume) 1 mg/m (dust and mist)
British Columbia	OEL TWA (mg/m)	1 mg/m (dust and mist) 0.2 mg/m (fume)
Manitoba	OEL TWA (mg/m)	0.2 mg/m (fume)
New Brunswick	OEL TWA (mg/m)	0.2 mg/m (fume) 1 mg/m (dust and mist)
Newfoundland & Labrador	OEL TWA (mg/m)	0.2 mg/m (fume)
Nova Scotia	OEL TWA (mg/m)	0.2 mg/m (fume)
Nunavut	OEL STEL (mg/m)	0.6 mg/m (fume) 2 mg/m (dust and mist)
Nunavut	OEL TWA (mg/m)	0.2 mg/m (fume) 1 mg/m (dust and mist)
Northwest Territories	OEL STEL (mg/m)	3 mg/m (dust and mist) 0.6 mg/m (fume)
Northwest Territories	OEL TWA (mg/m)	0.2 mg/m (fume) 1 mg/m (dust and mist)
Ontario	OEL TWA (mg/m)	0.2 mg/m (fume) 1 mg/m (dust and mist)
Prince Edward Island	OEL TWA (mg/m)	0.2 mg/m (fume)
Québec	VEMP (mg/m)	0.2 mg/m (fume) 1 mg/m (dust and mist)
Saskatchewan	OEL STEL (mg/m)	0.6 mg/m (fume) 3 mg/m (dust and mist)
Saskatchewan	OEL TWA (mg/m)	0.2 mg/m (fume) 1 mg/m (dust and mist)
Yukon	OEL STEL (mg/m)	0.2 mg/m (fume) 2 mg/m (dust and mist)
Yukon	OEL TWA (mg/m)	0.2 mg/m (fume) 1 mg/m (dust and mist)
Lead (7439-92-1)		
USA ACGIH	ACGIH TWA (mg/m)	0.05 mg/m
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans

USA ACGIH	Biological Exposure Indices (BEI)	30 g/100ml (Medium: blood - Time: not critical - Parameter: Lead (Note: Women of child bearing potential, whose blood Pb exceeds 10 g/dL, are at risk of delivering a child with a blood Pb over the current Centers for Disease Control guideline of 10 g/dL. If the blood Pb of such children remains elevated, they may be at increased risk of cognitive deficits. The blood Pb of these children should be closely monitored and appropriate steps should be taken to minimize the child's exposure to environmental lead.)
USA OSHA	OSHA PEL (TWA) (mg/m)	50 g/m
USA NIOSH	NIOSH REL (TWA) (mg/m)	0.050 mg/m
USA IDLH	US IDLH (mg/m)	100 mg/m
Alberta	OEL TWA (mg/m)	0.05 mg/m
British Columbia	OEL TWA (mg/m)	0.05 mg/m
Manitoba	OEL TWA (mg/m)	0.05 mg/m
New Brunswick	OEL TWA (mg/m)	0.05 mg/m
Newfoundland & Labrador	OEL TWA (mg/m)	0.05 mg/m
Nova Scotia	OEL TWA (mg/m)	0.05 mg/m
Nunavut	OEL STEL (mg/m)	0.45 mg/m
Nunavut	OEL TWA (mg/m)	0.15 mg/m
Northwest Territories	OEL STEL (mg/m)	0.15 mg/m
Northwest Territories	OEL TWA (mg/m)	0.05 mg/m
Ontario	OEL TWA (mg/m)	0.05 mg/m (designated substances regulation) 0.05 mg/m (applies to workplaces to which the designated substances regulation does not apply)
Prince Edward Island	OEL TWA (mg/m)	0.05 mg/m
Québec	VEMP (mg/m)	0.05 mg/m
Saskatchewan	OEL STEL (mg/m)	0.15 mg/m
Saskatchewan	OEL TWA (mg/m)	0.05 mg/m
Yukon	OEL STEL (mg/m)	0.45 mg/m (dust and fume)
Yukon	OEL TWA (mg/m)	0.15 mg/m (dust and fume)
Silver (7440-22-4)		
USA ACGIH	ACGIH TWA (mg/m)	0.1 mg/m (dust and fume)
USA OSHA	OSHA PEL (TWA) (mg/m)	0.01 mg/m
USA NIOSH	NIOSH REL (TWA) (mg/m)	0.01 mg/m (dust)
USA IDLH	US IDLH (mg/m)	10 mg/m (dust)
Alberta	OEL TWA (mg/m)	0.1 mg/m
British Columbia	OEL STEL (mg/m)	0.03 mg/m
British Columbia	OEL TWA (mg/m)	0.01 mg/m
Manitoba	OEL TWA (mg/m)	0.1 mg/m (dust and fume)

New Brunswick	OEL TWA (mg/m)	0.1 mg/m
Newfoundland & Labrador	OEL TWA (mg/m)	0.1 mg/m (dust and fume)
Nova Scotia	OEL TWA (mg/m)	0.1 mg/m (dust and fume)
Nunavut	OEL STEL (mg/m)	0.3 mg/m
Nunavut	OEL TWA (mg/m)	0.1 mg/m
Northwest Territories	OEL STEL (mg/m)	0.3 mg/m (metal)
Northwest Territories	OEL TWA (mg/m)	0.1 mg/m (metal)
Ontario	OEL TWA (mg/m)	0.1 mg/m (dust and fume)
Prince Edward Island	OEL TWA (mg/m)	0.1 mg/m (dust and fume)
Québec	VEMP (mg/m)	0.1 mg/m
Saskatchewan	OEL STEL (mg/m)	0.3 mg/m
Saskatchewan	OEL TWA (mg/m)	0.1 mg/m
Yukon	OEL STEL (mg/m)	0.03 mg/m
Yukon	OEL TWA (mg/m)	0.01 mg/m
Tin (7440-31-5)		
USA ACGIH	ACGIH TWA (mg/m)	2 mg/m
USA NIOSH	NIOSH REL (TWA) (mg/m)	2 mg/m
USA IDLH	US IDLH (mg/m)	100 mg/m
Alberta	OEL TWA (mg/m)	2 mg/m
British Columbia	OEL TWA (mg/m)	2 mg/m
Manitoba	OEL TWA (mg/m)	2 mg/m
New Brunswick	OEL TWA (mg/m)	2 mg/m
Newfoundland & Labrador	OEL TWA (mg/m)	2 mg/m
Nova Scotia	OEL TWA (mg/m)	2 mg/m
Northwest Territories	OEL STEL (mg/m)	4 mg/m (metal)
Northwest Territories	OEL TWA (mg/m)	2 mg/m (metal)
Ontario	OEL TWA (mg/m)	2 mg/m
Prince Edward Island	OEL TWA (mg/m)	2 mg/m
Québec	VEMP (mg/m)	2 mg/m
Saskatchewan	OEL STEL (mg/m)	4 mg/m
Saskatchewan	OEL TWA (mg/m)	2 mg/m
Aluminum (7429-90-5)		
USA ACGIH	ACGIH TWA (mg/m)	1 mg/m (respirable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m)	15 mg/m (total dust) 5 mg/m (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m)	10 mg/m (total dust) 5 mg/m (respirable dust)
Alberta	OEL TWA (mg/m)	10 mg/m (dust)
British Columbia	OEL TWA (mg/m)	1.0 mg/m (respirable)
Manitoba	OEL TWA (mg/m)	1 mg/m (respirable fraction)
New Brunswick	OEL TWA (mg/m)	10 mg/m (metal dust)
Newfoundland & Labrador	OEL TWA (mg/m)	1 mg/m (respirable fraction)
Nova Scotia	OEL TWA (mg/m)	1 mg/m (respirable fraction)
Nunavut	OEL STEL (mg/m)	20 mg/m
Nunavut	OEL TWA (mg/m)	10 mg/m

Northwest Territories	OEL STEL (mg/m)	20 mg/m (metal-dust)
Northwest Territories	OEL TWA (mg/m)	10 mg/m (metal-dust)
Ontario	OEL TWA (mg/m)	1 mg/m (respirable)
Prince Edward Island	OEL TWA (mg/m)	1 mg/m (respirable fraction)
Québec	VEMP (mg/m)	10 mg/m
Saskatchewan	OEL STEL (mg/m)	20 mg/m (dust)
Saskatchewan	OEL TWA (mg/m)	10 mg/m (dust)
Manganese (7439-96-5)		
USA ACGIH	ACGIH TWA (mg/m)	0.02 mg/m (respirable fraction)
0.1 mg/m (inhalable fraction)		
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (Ceiling) (mg/m)	5 mg/m (fume)
USA NIOSH	NIOSH REL (TWA) (mg/m)	1 mg/m (fume)
USA NIOSH	NIOSH REL (STEL) (mg/m)	3 mg/m
USA IDLH	US IDLH (mg/m)	500 mg/m
Alberta	OEL TWA (mg/m)	0.2 mg/m
British Columbia	OEL TWA (mg/m)	0.2 mg/m
Manitoba	OEL TWA (mg/m)	0.02 mg/m (respirable fraction) 0.1 mg/m (inhalable fraction)
New Brunswick	OEL TWA (mg/m)	0.2 mg/m
Newfoundland & Labrador	OEL TWA (mg/m)	0.02 mg/m (respirable fraction) 0.1 mg/m (inhalable fraction)
Nova Scotia	OEL TWA (mg/m)	0.02 mg/m (respirable fraction) 0.1 mg/m (inhalable fraction)
Nunavut	OEL Ceiling (mg/m)	5 mg/m
Nunavut	OEL STEL (mg/m)	3 mg/m (fume)
Nunavut	OEL TWA (mg/m)	1 mg/m (fume)
Northwest Territories	OEL STEL (mg/m)	0.6 mg/m
Northwest Territories	OEL TWA (mg/m)	0.2 mg/m
Ontario	OEL TWA (mg/m)	0.2 mg/m
Prince Edward Island	OEL TWA (mg/m)	0.02 mg/m (respirable fraction) 0.1 mg/m (inhalable fraction)
Québec	VEMP (mg/m)	0.2 mg/m (total dust and fume)
Saskatchewan	OEL STEL (mg/m)	0.6 mg/m
Saskatchewan	OEL TWA (mg/m)	0.2 mg/m
Yukon	OEL Ceiling (mg/m)	5 mg/m
Cobalt (7440-48-4)		
USA ACGIH	ACGIH TWA (mg/m)	0.02 mg/m
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA ACGIH	Biological Exposure Indices (BEI)	15 g/l (Medium: urine - Time: end of shift at end of work-week - Parameter: Cobalt (non-specific))
USA OSHA	OSHA PEL (TWA) (mg/m)	0.1 mg/m (dust and fume)
USA NIOSH	NIOSH REL (TWA) (mg/m)	0.05 mg/m (dust and fume)

USA IDLH	US IDLH (mg/m)	20 mg/m (dust and fume)
Alberta	OEL TWA (mg/m)	0.02 mg/m
British Columbia	OEL TWA (mg/m)	0.02 mg/m
Manitoba	OEL TWA (mg/m)	0.02 mg/m
New Brunswick	OEL TWA (mg/m)	0.02 mg/m
Newfoundland & Labrador	OEL TWA (mg/m)	0.02 mg/m
Nova Scotia	OEL TWA (mg/m)	0.02 mg/m
Nunavut	OEL STEL (mg/m)	0.3 mg/m (dust and fume)
Nunavut	OEL TWA (mg/m)	0.1 mg/m (metal-dust and fume)
Northwest Territories	OEL STEL (mg/m)	0.06 mg/m
Northwest Territories	OEL TWA (mg/m)	0.02 mg/m
Ontario	OEL TWA (mg/m)	0.02 mg/m
Prince Edward Island	OEL TWA (mg/m)	0.02 mg/m
Québec	VEMP (mg/m)	0.02 mg/m
Saskatchewan	OEL STEL (mg/m)	0.06 mg/m
Saskatchewan	OEL TWA (mg/m)	0.02 mg/m
Yukon	OEL STEL (mg/m)	0.15 mg/m (dust and fume)
Yukon	OEL TWA (mg/m)	0.05 mg/m (dust and fume)
Phosphorus elemental (7723-14-0)		
Alberta	OEL TWA (mg/m)	0.1 mg/m (yellow)
New Brunswick	OEL TWA (mg/m)	0.1 mg/m (yellow)
New Brunswick	OEL TWA (ppm)	0.02 ppm (yellow)
Québec	VEMP (mg/m)	0.1 mg/m (yellow)
Silicon (7440-21-3)		
USA OSHA	OSHA PEL (TWA) (mg/m)	15 mg/m (total dust) 5 mg/m (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m)	10 mg/m (total dust) 5 mg/m (respirable dust)
British Columbia	OEL TWA (mg/m)	10 mg/m (total dust) 3 mg/m (respirable fraction)
New Brunswick	OEL TWA (mg/m)	10 mg/m
Nunavut	OEL TWA (mg/m)	5 mg/m (respirable mass) 10 mg/m (total mass)
Northwest Territories	OEL STEL (mg/m)	20 mg/m
Northwest Territories	OEL TWA (mg/m)	10 mg/m
Québec	VEMP (mg/m)	10 mg/m (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m)	20 mg/m
Saskatchewan	OEL TWA (mg/m)	10 mg/m
Yukon	OEL STEL (mg/m)	20 mg/m
Yukon	OEL TWA (mg/m)	30 mppcf 10 mg/m
Antimony (7440-36-0)		
USA ACGIH	ACGIH TWA (mg/m)	0.5 mg/m
USA OSHA	OSHA PEL (TWA) (mg/m)	0.5 mg/m
USA NIOSH	NIOSH REL (TWA) (mg/m)	0.5 mg/m
USA IDLH	US IDLH (mg/m)	50 mg/m

Alberta	OEL TWA (mg/m)	0.5 mg/m
British Columbia	OEL TWA (mg/m)	0.5 mg/m
Manitoba	OEL TWA (mg/m)	0.5 mg/m
New Brunswick	OEL TWA (mg/m)	0.5 mg/m
Newfoundland & Labrador	OEL TWA (mg/m)	0.5 mg/m
Nova Scotia	OEL TWA (mg/m)	0.5 mg/m
Nunavut	OEL STEL (mg/m)	1.5 mg/m
Nunavut	OEL TWA (mg/m)	0.5 mg/m
Northwest Territories	OEL STEL (mg/m)	1.5 mg/m
Northwest Territories	OEL TWA (mg/m)	0.5 mg/m
Ontario	OEL TWA (mg/m)	0.5 mg/m
Prince Edward Island	OEL TWA (mg/m)	0.5 mg/m
Québec	VEMP (mg/m)	0.5 mg/m
Saskatchewan	OEL STEL (mg/m)	1.5 mg/m
Saskatchewan	OEL TWA (mg/m)	0.5 mg/m
Yukon	OEL STEL (mg/m)	0.75 mg/m
Yukon	OEL TWA (mg/m)	0.5 mg/m

8.2. Exposure Controls

Appropriate Engineering Controls: Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective clothing. Gloves. Safety glasses. Dust formation: dust mask. Insufficient ventilation: wear respiratory protection.

Materials for Protective Clothing: Chemically resistant materials and fabrics. With molten material wear thermally protective clothing.

Hand Protection: Wear chemically resistant protective gloves. If material is hot, wear thermally resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing. Wash contaminated clothing before reuse.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Thermal Hazard Protection: If material is hot, wear thermally resistant protective

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	Solid
Appearance	Reddish-brown
Odor	None
Odor Threshold	Not available
pH	Not available
Evaporation Rate	Not available
Melting Point	866 - 1038 C (1590.8 - 1900.4 F)

Freezing Point	Not available
Boiling Point	Not available
Flash Point	Not applicable
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Flammability (solid, gas)	Not available
Lower Flammable Limit	Not available
Upper Flammable Limit	Not available
Vapor Pressure	Not available
Relative Vapor Density at 20 C	Not available
Relative Density	Not available
Specific gravity / density/lbs/in³	.397
Specific Gravity Kg/m³	8.94
Solubility	Insoluble in water
Partition Coefficient: N-Octanol/Water	Not available
Viscosity	Not available
Explosion Data -	
Sensitivity to Mechanical Impact	Not expected to present an explosion hazard due to mechanical impact.
Sensitivity to Static Discharge	Take precautions against static discharge where there is a risk of dust explosion.,Static discharge could act as an ignition source.
VOC content	0%

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Dust and other forms of product formed from processing might react with water producing a flammable/explosive.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7). Dust, chips or ribbons can be ignited more easily.

10.3. Possibility of Hazardous Reactions: Molten metal and water may be explosive.

10.4. Conditions to Avoid: Avoid creating or spreading dust. Sparks, heat, open flame and other sources of ignition. Dust, chips, or ribbons can be ignited more easily, by an ignition source, by improper machining, or by spontaneous combustion if finely divided and damp.

10.5. Incompatible Materials: When molten: water. Strong acids, strong bases, strong oxidizers. Alkalis. Metal oxides. Moisture. Corrosive substances in contact with metals may produce flammable hydrogen gas.

10.6. Hazardous Decomposition Products: Thermal decomposition generates: Metal oxides, fume, carbon monoxide, carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Oral: Not classified Inhalation: dust,mist: Not classified.

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory/Skin Sensitization:	Not classified
Germ Cell Mutagenicity:	Not classified
Teratogenicity:	Not available
Carcinogenicity:	Not classified
Reproductive Toxicity:	Not classified
Specific Target Organ Toxicity (Repeated Exposure):	Not classified
Specific Target Organ Toxicity (Single Exposure):	Not classified
Aspiration Hazard:	Not classified

Symptoms/Injuries After Inhalation: Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Dust from physical alteration of this product causes skin irritation. Causes severe skin burns. Contact with fumes or metal powder will irritate skin. Contact with hot, molten metal will cause thermal burns. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Mechanical damage via flying particles and chipped slag is possible.

Symptoms/Injuries After Eye Contact: Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: In massive form, no hazard exists. **If physically altered to present slivers, ribbons, dusts or fumes from molten material:** Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. Nickel: May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. Inhalation of Nickel compounds has been shown in studies to provide an increased incidence of cancer of the nasal cavity, lung and possibly larynx in nickel refinery workers. Copper: Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever, dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair. Tissue damage of mucous membranes may follow chronic dust exposure. Silicon: Can cause chronic bronchitis and narrowing of the airways. Zinc: Prolonged exposure to high concentrations of zinc fumes may cause "zinc shakes", an involuntary twitching of the muscles. Otherwise, zinc is non-toxic. Silver: Chronic skin contact or ingestion of silver dust, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes. Inhalation of iron oxide fumes undergoing decomposition may cause irritation and flu-like symptoms, otherwise iron oxide is not hazardous. Manganese: Chronic exposure can cause inflammation of the lung tissue, scarring the lungs (pulmonary fibrosis). Chronic exposure to excessive manganese levels can lead to a variety of psychiatric and motor disturbances, termed manganism. Chromium: Certain hexavalent chromium compounds have been demonstrated to be carcinogenic on the basis of epidemiological investigations on workers and experimental studies in animals. Increased incidences of respiratory cancer have been found in chromium (VI) workers. There is an increased incidence of lung cancer in industrial workers exposed to chromium (VI) compounds. Please refer to IARC volume 23 for a more detailed discussion.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Nickel (7440-02-0)	
LD50 Oral Rat	> 9000 mg/kg
Tin (7440-31-5)	
LD50 Oral Rat	700 mg/kg
Iron (7439-89-6)	

LD50 Oral Rat	984 mg/kg
ATE US (oral)	984.00 mg/kg body weight
Manganese (7439-96-5)	
LD50 Oral Rat	> 2000 mg/kg
LC50 Inhalation Rat	> 5.14 mg/l/4h
Cobalt (7440-48-4)	
LD50 Oral Rat	215.9 - 1140 mg/kg
LC50 Inhalation Rat	> 10 mg/l (Exposure time: 1 h)
ATE US (oral)	215.90 mg/kg body weight
Phosphorus elemental (7723-14-0)	
LD50 Oral Rat	3030 g/kg
LD50 Dermal Rat	100 mg/kg
LC50 Inhalation Rat	4.3 mg/l (Exposure time: 1 h)
ATE US (oral)	3.03 mg/kg body weight
ATE US (dermal)	100.00 mg/kg body weight
ATE US (vapors)	4.30 mg/l/4h
ATE US (dust, mist)	4.30 mg/l/4h
Silicon (7440-21-3)	
LD50 Oral Rat	3160 mg/kg
ATE US (oral)	3,160.00 mg/kg body weight
Antimony (7440-36-0)	
LD50 Oral Rat	100 mg/kg
ATE US (oral)	100.00 mg/kg body weight
Nickel (7440-02-0)	
IARC Group	2B
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Lead (7439-92-1)	
IARC Group	2A
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Cobalt (7440-48-4)	
IARC Group	2B
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity No additional information available Nickel (7440-02-0)

LC50 Fish 1	100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
EC50 Daphnia 1	121.6 g/l (Exposure time: 48h - Species: Ceriodaphnia dubia [static])
LC 50 Fish 2	15.3 mg/l
EC50 Daphnia 2	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

EC50 Other Aquatic Organisms 2	0.174 (0.174 - 0.311) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])
Copper (7440-50-8)	
LC50 Fish 1	0.0068 (0.0068 - 0.0156) mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 1	0.0426 (0.0426 - 0.0535) mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
LC 50 Fish 2	0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	0.031 (0.031 - 0.054) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])
Lead (7439-92-1)	
LC50 Fish 1	0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi static])
EC50 Daphnia 1	600 g/l (Exposure time: 48 h - Species: water flea)
LC 50 Fish 2	1.17 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
Zinc (7440-66-6)	
LC50 Fish 1	2.16 - 3.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.139 - 0.908 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	0.211 - 0.269 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])
ErC50 (algae)	0.15 mg/l
Manganese (7439-96-5)	
NOEC chronic fish	3.6 mg/l (Exposure time: 96h; Species: Oncorhynchus mykiss)
Cobalt (7440-48-4)	
LC50 Fish 1	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
Phosphorus elemental (7723-14-0)	
LC50 Fish 1	33.2 mg/l Red Phosphorous (Exposure time: 96 h - Species Danio rerio [static])
EC50 Daphnia 1	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	0.001 - 0.004 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 2	0.025 - 0.037 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and Degradability

Bronze Alloys	Persistence and Degradability	May cause long-term adverse effects in the environment	Not readily biodegradable
----------------------	--------------------------------------	---	----------------------------------

12.3. Bioaccumulative Potential

Not established

12.4. Mobility in Soil

Not available

12.5. Other Adverse Effects

Other Information:

Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Treatment Methods: Recycle product or dispose properly.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT	Not regulated for transport
14.2. In Accordance with IMDG	Not regulated for transport
14.3. In Accordance with IATA	Not regulated for transport
14.4. In Accordance with TDG	Not regulated for transport

SECTION 15: DISPOSAL INFORMATION

15.1. US Federal Regulations

Nickel (7440-02-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	100 lb (only applicable if particles are < 100 m)
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Delayed (chronic) health hazard	
SARA Section 313 - Emission Reporting	0.1 %
Copper (7440-50-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %
Lead (7439-92-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	0.1 %
Silver (7440-22-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	1000 lb < 100 um
CERCLA/SARA RQ CHANGE TITLE	
SARA Section 313 - Emission Reporting	1.0 %

Tin (7440-31-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Zinc (7440-66-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 % (dust or fume only)
Aluminum (7429-90-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Fire hazard
Reactive hazard	
SARA Section 313 - Emission Reporting	1.0 % (dust or fume only)
Iron (7439-89-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Manganese (7439-96-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %
Cobalt (7440-48-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
SARA Section 313 - Emission Reporting	0.1 %
Phosphorus elemental (7723-14-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ)	100 (This material is a reactive solid. The TPQ does not default to 10000 pounds for non-powder, non-molten, non-solution form)
SARA Section 313 - Emission Reporting	1.0 % (yellow or white)
Silicon (7440-21-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Antimony (7440-36-0)	

Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %

15.2. US State Regulations

Nickel (7440-02-0)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Lead (7439-92-1)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
U.S. - California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of California to cause birth defects.
U.S. - California - Proposition 65 - Reproductive Toxicity -	
Female	WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm.
U.S. - California - Proposition 65 - Reproductive Toxicity -	
Male	WARNING: This product contains chemicals known to the State of California to cause (Male) reproductive harm.
Cobalt (7440-48-4)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

Nickel (7440-02-0)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

U.S. - Pennsylvania - RTK (Right to Know) List

Copper (7440-50-8)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

Lead (7439-92-1)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

Silver (7440-22-4)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

Tin (7440-31-5)

- U.S. - Massachusetts - Right To Know List**
- U.S. - New Jersey - Right to Know Hazardous Substance List**
- U.S. - Pennsylvania - RTK (Right to Know) List**

Zinc (7440-66-6)

- U.S. - Massachusetts - Right To Know List**
- U.S. - New Jersey - Right to Know Hazardous Substance List**
- U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**
- U.S. - Pennsylvania - RTK (Right to Know) List**

Aluminum (7429-90-5)

- U.S. - Massachusetts - Right To Know List**
- U.S. - New Jersey - Right to Know Hazardous Substance List**
- U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**
- U.S. - Pennsylvania - RTK (Right to Know) List**

Manganese (7439-96-5)

- U.S. - Massachusetts - Right To Know List**
- U.S. - New Jersey - Right to Know Hazardous Substance List**
- U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**
- U.S. - Pennsylvania - RTK (Right to Know) List**

Cobalt (7440-48-4)

- U.S. - Massachusetts - Right To Know List**
- U.S. - New Jersey - Right to Know Hazardous Substance List**
- U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**
- U.S. - Pennsylvania - RTK (Right to Know) List**

Phosphorus elemental (7723-14-0)

- U.S. - Massachusetts - Right To Know List**
- U.S. - New Jersey - Right to Know Hazardous Substance List**
- U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**
- U.S. - Pennsylvania - RTK (Right to Know) List**

Silicon (7440-21-3)

- U.S. - Massachusetts - Right To Know List**
- U.S. - New Jersey - Right to Know Hazardous Substance List**
- U.S. - Pennsylvania - RTK (Right to Know) List**

Antimony (7440-36-0)

- U.S. - Massachusetts - Right To Know List**
- U.S. - New Jersey - Right to Know Hazardous Substance List**
- U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**
- U.S. - Pennsylvania - RTK (Right to Know) List**

15.3. Canadian Regulations

Bronze Alloys

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Nickel (7440-02-0)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 0.1 %	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	

Copper (7440-50-8)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Lead (7439-92-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 0.1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Tin (7440-31-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Zinc (7440-66-6)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Aluminum (7429-90-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 6 - Reactive Flammable Material
Class B Division 4 - Flammable Solid	
Iron (7439-89-6)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Manganese (7439-96-5)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Cobalt (7440-48-4)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 0.1 %	
WHMIS Classification	Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects
Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects	
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Phosphorus elemental (7723-14-0)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 4 - Flammable Solid
Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects	
Class E - Corrosive Material	
Silicon (7440-21-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Antimony (7440-36-0)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	

WHMIS Classification **Uncontrolled product according to WHMIS classification criteria** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 08/24/2016

Other Information : This document has been prepared in accordance with the