


Aluminum Rod & Bar

6061 - T6511 Rectangular Bar



- Specifications: ASTM B 221
- Stocked in 12 foot lengths, sharp corners

| Thickness (A) | Width (B) | Lbs/Ft | Lbs/Length | Part Number |
|---------------|-----------|--------|------------|-------------|
| $1/8$ | $3/4$ | 0.110 | 1.320 | 262123 |
| | 1 | 0.147 | 1.764 | 135538 |
| | $1 1/4$ | 0.187 | 2.244 | 135546 |
| | $1 1/2$ | 0.220 | 2.640 | 130473 |
| | 2 | 0.294 | 3.528 | 135554 |
| | 3 | 0.450 | 5.400 | 435035 |
| | 4 | 0.600 | 7.200 | 435043 |
| $3/16$ | $3/4$ | 0.168 | 2.020 | 507670 |
| | 1 | 0.220 | 2.640 | 135562 |
| | $1 1/4$ | 0.282 | 3.384 | 431324 |
| | $1 1/2$ | 0.330 | 3.960 | 135570 |
| | 2 | 0.441 | 5.292 | 135588 |
| | $2 1/2$ | 0.560 | 6.720 | 431332 |
| | 3 | 0.661 | 7.932 | 135596 |
| | 4 | 0.902 | 10.824 | 496975 |
| $1/4$ | $1/2$ | 0.150 | 1.800 | 452215 |
| | $3/4$ | 0.221 | 2.652 | 466387 |
| | 1 | 0.294 | 3.528 | 135601 |
| | $1 1/4$ | 0.367 | 4.404 | 135619 |
| | $1 1/2$ | 0.441 | 5.292 | 135627 |
| | 2 | 0.587 | 7.044 | 135635 |
| | $2 1/2$ | 0.735 | 8.820 | 286907 |
| | 3 | 0.881 | 10.572 | 135643 |
| | $3 1/2$ | 1.029 | 12.348 | 464199 |
| | 4 | 1.170 | 14.040 | 135651 |
| | 5 | 1.470 | 17.640 | 468135 |
| | 6 | 1.764 | 21.168 | 135669 |
| $3/8$ | $1/2$ | 0.221 | 2.652 | 466395 |
| | $3/4$ | 0.330 | 3.960 | 466400 |
| | 1 | 0.441 | 5.292 | 135677 |
| | $1 1/4$ | 0.563 | 6.756 | 431340 |
| | $1 1/2$ | 0.661 | 7.932 | 135685 |
| | 2 | 0.881 | 10.572 | 135693 |
| | $2 1/2$ | 1.100 | 13.200 | 135708 |
| | 3 | 1.320 | 15.840 | 135716 |
| | 4 | 1.760 | 21.120 | 135732 |
| | 5 | 2.205 | 26.460 | 402367 |
| | 6 | 2.646 | 31.750 | 255134 |
| | 10 | 4.410 | 52.920 | 634948 |
| $1/2$ | $3/4$ | 0.449 | 5.388 | 421816 |
| | 1 | 0.590 | 7.080 | 135740 |
| | $1 1/4$ | 0.749 | 8.988 | 431358 |
| | $1 1/2$ | 0.880 | 10.560 | 135758 |
| | $1 3/4$ | 1.029 | 12.348 | 431366 |

| Thickness (A) | Width (B) | Lbs/Ft | Lbs/Length | Part Number |
|---------------|-----------|--------|------------|-------------|
| $1/2$ | 2 | 1.170 | 14.040 | 135766 |
| | $2 1/2$ | 1.470 | 17.640 | 135774 |
| | 3 | 1.760 | 21.120 | 135782 |
| | $3 1/2$ | 2.060 | 24.720 | 288810 |
| | 4 | 2.350 | 28.200 | 135790 |
| | 5 | 2.998 | 35.976 | 435378 |
| | 6 | 3.530 | 42.360 | 135805 |
| | 8 | 4.704 | 56.448 | 555495 |
| $5/8$ | 1 | 0.749 | 8.988 | 431374 |
| | $1 1/2$ | 1.103 | 13.236 | 490360 |
| | 2 | 1.500 | 18.000 | 431382 |
| | $2 1/2$ | 1.870 | 22.440 | 135813 |
| | 12 | 8.820 | 105.840 | 631445 |
| $3/4$ | 1 | .882 | 10.584 | 417401 |
| | $1 1/4$ | 1.126 | 13.512 | 449660 |
| | $1 1/2$ | 1.323 | 15.876 | 417419 |
| | 2 | 1.760 | 21.120 | 135821 |
| | $2 1/2$ | 2.200 | 26.400 | 135839 |
| | 3 | 2.650 | 31.800 | 135847 |
| | 4 | 3.600 | 43.200 | 135855 |
| | 5 | 4.410 | 52.920 | 505000 |
| | 6 | 5.292 | 63.500 | 255142 |
| | 8 | 7.056 | 84.672 | 555500 |
| | 10 | 8.820 | 105.840 | 494314 |
| | 12 | 10.584 | 127.008 | 621929 |
| 1 | $1 1/4$ | 1.470 | 17.640 | 277550 |
| | $1 1/2$ | 1.799 | 21.588 | 130449 |
| | 2 | 2.399 | 26.788 | 235249 |
| | $2 1/2$ | 3.000 | 36.000 | 256384 |
| | 3 | 3.530 | 42.360 | 404173 |
| | $3 1/2$ | 4.116 | 49.392 | 512497 |
| | 4 | 4.700 | 56.400 | 405917 |
| | 5 | 5.880 | 70.560 | 294780 |
| | 6 | 7.060 | 84.720 | 135863 |
| | 8 | 9.600 | 155.200 | 510762 |
| | 12 | 14.112 | 169.340 | 509672 |
| $1 1/4$ | $1 1/2$ | 2.205 | 26.460 | 486094 |
| | 2 | 3.000 | 36.000 | 256342 |
| | $2 1/2$ | 3.675 | 44.100 | 476154 |
| | 3 | 4.500 | 54.000 | 431390 |
| | 4 | 6.000 | 72.000 | 431405 |
| | 6 | 8.820 | 105.840 | 512489 |
| $1 1/2$ | 2 | 3.599 | 43.188 | 431413 |
| | $2 1/2$ | 4.410 | 52.920 | 463876 |

Dimensions are in inches. All weights are approximate.